

KANSAS CORRECTIONAL INDUSTRIES WATER BASED DARK GRAY FLOOR PAINT

SAFETY DATA SHEET


SECTION 1 – PRODUCT NAME AND COMPANY IDENTIFICATION

1.1 Product name: Water Based Dark Gray Floor Paint
 General use: Paint
 Product description: Opaque gray liquid
 Product number(s): Water Based Dark Gray Floor Paint

1.2 Manufacturer: Kansas Correctional Industries, 4th. St. & Kansas St., Lansing, KS 66043
 Telephone number: (913) - 727 - 3249
 Emergency number: Chemtrec: (800) - 424 - 9300

Date prepared: June 23, 2022; supersedes any previous editions
 Prepared by Kinetic Solutions (423-802-0684, petersteyn@msn.com)

SECTION 2 – HAZARDS IDENTIFICATION

2.1	Classification of the substance:	Cat. 3, Skin	Cat. 2A, Eye		GHS07
2.2	Signal word:	WARNING			
2.3	Hazard statement:	H302:	Harmful if swallowed.		
		H315:	Causes skin irritation.		
		H319:	Causes serious eye irritation.		
2.4	Precautionary prevention statements:	P102:	Keep out of reach of children.		
		P264:	Wash exposed skin thoroughly after handling.		
		P280:	Wear protective gloves/protective clothing/eye protection/face protection.		
2.5	Precautionary response statements	P312:	Call a POISON CENTER or doctor/physician if you feel unwell.		
		P301, P330, P331:	IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.		
		P302, P352:	IF ON SKIN: Wash with plenty of water.		
		P304, P340:	IF INHALED: Remove victim to fresh air, rest in a position comfortable for breathing.		
		P305, P351, P338:	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing as needed.		
		P362, P364:	Take off contaminated clothing and wash before reuse.		
		P337, P313:	If eye irritation persists: Get medical advice / attention.		
2.6	Precautionary disposal statement:	P501:	Dispose of contents / container in accordance with local / national / international regulations.		
2.7	NFPA / HMIS rating:	2, 0, 0, B			

SECTION 3 – COMPOSITION / INFORMATION ON INGREDIENTS

	CAS #	% by wt.	<u>OSHA PEL</u> PPM mg/m ³	<u>ACGIH TLV</u> PPM mg/m ³	<u>NIOSH / IDLH</u> mg/m ³ mg/m ³	SARA TITLE III	RQ (lbs.)
3.1 Hazardous components:							
Trimethylpentanediol isobutyl ether	25265-77-4	< 3%	Not est.	Not est.	Not est.	Not listed	None
Titanium dioxide (dust)	13463-67-7	< 10%	10	10	5000	311 / 312	None

The remaining components of this product are non-hazardous or are in small enough quantities as to not meet regulatory thresholds for disclosure.
 These components contain no substances or impurities which would influence the classification of this product.
 All components and their specific proportions in this product are considered proprietary to Kansas Correctional Industries.

KANSAS CORRECTIONAL INDUSTRIES WATER BASED DARK GRAY FLOOR PAINT

SECTION 4 – FIRST AID MEASURES

- 4.1 Description of first aid measures
- General information: Immediately remove any clothing soiled by the product. Always seek medical help for any exposure.
After inhalation: In case of unconsciousness place patient stably in a side position for transportation. Supply fresh air. If required, provide artificial respiration. Keep patient warm.
After skin contact: Immediately rinse with water. Seek immediate medical advice.
After eye contact: Remove contact lenses if worn. Rinse eye for several minutes under running water. Seek medical advice.
After swallowing: Do not induce vomiting; call for medical help immediately. Rinse out mouth and then drink plenty of water. A person vomiting while on their back should be turned onto their side.

SECTION 5 – FIRE FIGHTING PROCEDURES

- 5.1 Extinguishing media: Carbon dioxide, water fog, chemical foam, dry chemical. Material is non-flammable.
5.2 General hazards: Material is irritating, avoid contact and conditions that result in agitating or foaming the material.
5.3 Advice for firefighters: **Up to 600 mg/m³**: APF = 50; Any self-contained breathing apparatus with a full facepiece.
Entry into unknown concentrations or IDLH conditions: APF = 10,000; any self-contained breathing apparatus that has a full facepiece and is operated in a pressure-demand mode.
that has a full facepiece and is operated in a pressure-demand mode.
5.4 Unusual hazards: None.
5.5 Firefighting procedures: Keep containers cool with water spray to prevent container rupture due to steam buildup; floor will become slippery if material is released. Material is alkaline and will irritate the eyes if product or fumes contact the eyes.
5.6 Decomposition compounds: Oxides of carbon, sodium, titanium, and nitrogen may be released with sufficient thermal energy.

SECTION 6 – ACCIDENTAL RELEASE MEASURES

- 6.1 Protective equipment and emergency procedures: Wear protective equipment. Keep unprotected persons away. Particular danger of slipping on leaked / spilled product. Ensure adequate ventilation, material is irritating, avoid direct contact.
6.2 Environmental precautions: Dilute with plenty of water and do not allow it to enter sewers, surface, or ground water.
6.3 Methods and materials for containment and clean up: Absorb with liquid-binding material (sand, diatomite, universal binders, sawdust). Use neutralizing agent. Clean the affected area carefully, dispose contaminated material as waste according to Section 13.
6.4 Reference to other sections: See Section 7 for information on safe handling. See Section 8 for information on personal protection equipment.

SECTION 7 – HANDLING AND STORAGE

- 7.1 Precautions for safe handling: Ensure good ventilation/exhaustion at the workplace. Prevent formation of aerosols and dusts.
7.2 Conditions for safe storage: Do not store together with acids or foodstuffs. Store in cool, dry conditions in well sealed receptacles.
7.3 Specific end use(s): No further relevant information available.

SECTION 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

- 8.1 Exposure controls:
- General protective and hygienic measures:** Keep away from foodstuffs and beverages. Immediately remove all soiled and contaminated clothing. Wash hands before breaks and at the end of work. Avoid direct contact with the eyes and skin. Limit personal exposure to open containers or vessels in enclosed spaces, do not smoke or cause an ignition source when handling or storing product.
- Respiratory protection:** None required unless product is aerated, dusted, or sprayed.
- Protection of hands:** Protective gloves, the glove material has to be impermeable and resistant to the product, such as neoprene, butyl, or nitrile rubber gloves with cuffs.
- Eye protection:** Safety glasses and / or goggles with side shields.
- Body protection:** Protective work clothing.

KANSAS CORRECTIONAL INDUSTRIES WATER BASED DARK GRAY FLOOR PAINT

SECTION 9 – PHYSICAL AND CHEMICAL PROPERTIES

9.1	Appearance:	Light gray viscous liquid
	Odor:	Characteristic
	Odor threshold:	ND
	pH:	8.0 - 9.0
	Kinematic viscosity:	3000 cSt
	Melting point / freezing point:	ND
	Initial boiling point and boiling range:	ND
	Flash point:	None
	Evaporation rate:	ND
	Flammability (solid, gas):	Not flammable
	Upper / lower flammability or explosive limits:	ND
	Vapor pressure:	ND
	Vapor density:	ND
	Relative density:	1.11 @ 25°C
	Solubility:	Soluble in water
	Partition coefficient: n-octanol/water:	ND
	Autoignition temperature:	ND
	Decomposition temperature:	ND
9.2	Other information:	None

SECTION 10 –STABILITY AND REACTIVITY

10.1	Reactivity:	No spontaneous reactivity
10.2	Chemical stability:	Thermal decomposition possible at temperatures exceeding 600°F.
10.3	Possible hazardous reactions:	None.
10.4	Conditions to avoid:	No further relevant information available.
10.5	Incompatible materials:	Strong oxidizers and acids.
10.6	Decomposition products:	Oxides of carbon, sodium, titanium, and nitrogen.

SECTION 11 – TOXICOLOGICAL INFORMATION

11.1	Hazardous Ingredients	CAS #	EINECS #	LD 50, species / route
	Trimethylpentanediol isobutyl ether	25265-77-4	77-68-9	LD50, Rat, oral, > 1,000 mg/kg
	Titanium dioxide	13463-67-7	236-675-5	LD50, Rat, oral, > 5,000 mg/kg
11.2	Serious eye damage/irritation:	No data available		
11.3	Respiratory or skin sensitization:	No data available		
11.4	Repeated dose toxicity:	No data available		
11.5	STOT (single/repeated)	No data available		
11.6	Carcinogenicity:	No data available		
11.7	Mutagenicity:	No data available		
11.8	Reproductive toxicity:	No data available		

SECTION 12 – ECOLOGICAL INFORMATION

12.1	Toxicity:	Trimethylpentanediol isobutyl ether	LC50, Fathead minnow, 33mg/liter (96 hours)
		Titanium dioxide	LC50, Fathead minnow, > 5,000 mg/liter (96 hours)
		Finished product:	No available data.
12.2	Persistence and degradability:	Expected to be easily biodegradable based on composition.	
12.3	Bioaccumulative potential:	Not expected to exhibit this behavior based on composition.	
12.4	Soil mobility:	No specific data available.	
12.5	General information:	No data are available on the adverse effects of this material on the environment. Neither COD nor BOD data are available. Based on the chemical composition of this product it is assumed that the mixture can be treated in an acclimatized biological waste treatment plant system in limited quantities. However, such treatment should be evaluated and approved for each specific biological system. None of the ingredients in this mixture are classified as a Marine Pollutant.	

KANSAS CORRECTIONAL INDUSTRIES WATER BASED DARK GRAY FLOOR PAINT

SECTION 13 – DISPOSAL CONSIDERATIONS

- 13.1 Waste treatment methods: It is recommended that small amounts may be diluted with plenty of water and washed away. Dispose of bigger amounts in accordance with local requirements. Refer to 40 CFR 260 - 299 for complete waste disposal regulations for alkaline materials. Consult your local, state, or federal agency before disposing of any chemicals.

SECTION 14 – TRANSPORTATION INFORMATION

- 14.1 UN number: None
DOT, ADR, IMDG, IATA
- 14.2 Proper shipping name: Paint
DOT, ADR, IMDG, IATA
- 14.3 Transport hazard class: None
DOT, ADR, IMDG, IATA
- 14.4 Packing group: III
DOT, ADR, IMDG, IATA
- 14.5 Environmental hazards: None
Marine

Note: Transportation information provided is for reference only. Customer is urged to consult 49 CFR 100 - 177, IMDG, IATA, EC, United Nations TDG, and WHMIS (Canada) TDG information manuals for detailed regulations and exceptions covering specific container sizes, packaging materials and methods of shipping.

SECTION 15 – REGULATORY INFORMATION

- 15.1 TSCA: All components of this product are listed on the U.S. Toxic Substances Control Act Chemical Inventory (TSCA Inventory) or are exempted from listing because a Low Volume Exemption has been granted in accordance with 40 CFR 723.50.
- 15.2 SARA TITLE III: Not regulated under 302, 303. Regulated under 311 / 312.
- 15.3 CERCLA: Not listed
- 15.4 Clean Air Act: No ingredients defined as Hazardous Air Pollutants or Stratospheric Ozone Depleting.
- 15.5 California Prop. 65: Not listed.
- 15.6 Right To Know: Not listed.
- 15.7 CPR classification: WHMIS Classification: None
- 15.8 Canadian IDL: Components of this product identified by CAS number and listed on the Canadian Ingredient Disclosure List are shown in Section 2.
- 15.9 Can. DSL / NDSL: Components of this product identified by CAS number are listed on the DSL or NDSL or are otherwise in compliance with the New Substances Notification (NSN) regulations. Only ingredients classified as "hazardous" are listed in Section 2 unless otherwise indicated.
- 15.10 EINECS: Components of this product identified by CAS numbers are on the European Inventory of Existing Commercial Chemical Substances.

SECTION 16 – OTHER INFORMATION

- 16.1 Risk phrases: R36 / 37 / 38: Irritating to the eyes / respiratory system / skin
Safety phrases: S36 / 37 / 39: Wear protective clothing, gloves, and eye / face protection.

Symbols for label:



- Definitions:
- | | |
|-----------------|----------------------------------------------------------------------------------------------------|
| OSHA PEL: | Occupational Safety and Health Act; Personal Exposure Limit |
| ACGIH TLV: | American Conference of Governmental Industrial Hygienists: Threshold Limit Values |
| NIOSH REL: | National Institute for Occupational Safety and Health: Recommended Exposure Limits |
| IDLH: | Immediate Danger to Life and Health |
| SARA TITLE III: | Superfund Amendment and Reauthorization Act,
Emergency Planning and Community Right-to-Know Act |
| RQ: | Reportable quantity |
| APF: | Assigned Protection Factor |
| DOT: | Department of Transportation |
| ADR: | Agreement Concerning the International Carriage of Dangerous Goods by Road |
| MDG: | Maritime Dangerous Goods Code |
| IATA: | International Air Transport Association |
| TSCA: | Toxic Substance Control Act |
| CERCLA: | Comprehensive Environmental Response, Compensation, and Liability Act |
| WHMIS: | Workplace Hazardous Materials Information System (Canada) |

Terms and Conditions. This SDS is designed only as guidance for the products to which it applies. To the greatest extent permitted by applicable law, nothing contained herein creates any legal obligation including contractual obligations, expressed or implied warranties, including any warranties of use or fitness for particular purpose. The information contained herein is based on the manufacturer's own study and the work of others and is subject to change at any time without further notice. There is no warranty, expressed or implied, as to the accuracy, completeness or adequacy of the information contained herein, and neither the provider nor the manufacturer (nor the agents, directors, officers, contractors or employees of either) are liable to any party for any damages of any nature, including direct, special or consequential damages arising out of or in connection with the accuracy, completeness, adequacy or furnishing of any information in this SDS, or in any other way related (directly or indirectly) to this SDS. The receipt and use of this information constitutes consent to these terms and conditions.